Dean&Francis

ISSN 2959-6157

Current Development and Application Prospects of Brain-Computer Interface Technology

Yifan Wang[1, *]

[1]school of SHHD high school, Shanghai, China
*Corresponding author: wangyifan20080208@163.com

Abstract:

Brain-Computer Interface (BCI) technology establishes a direct communication pathway between the human brain and external devices, bypassing conventional peripheral nerve and muscle outputs. This comprehensive review delineates the fundamental architecture, core computational algorithms, and burgeoning applications of BCI systems within medical rehabilitation and consumer electronics. It further critically examines prevailing technical impediments, such as limitations in signal fidelity, model generalizability across subjects, and pressing ethical considerations regarding neural data privacy and manipulation. Prospective development trajectories, including hybrid system design, adaptive algorithmic frameworks based on meta-learning, and standardized governance models, are elaborated. The analysis substantiates that BCI technology possesses considerable potential to augment human functional capabilities and quality of life, with its full maturation contingent upon sustained interdisciplinary collaboration among neuroscientists, engineers, ethicists, and clinical practitioners. This review aims to provide a consolidated reference for navigating the rapidly evolving BCI landscape.

Keywords: Brain-Computer Interface (BCI); Electroencephalography (EEG); Neural Signal Decoding; Medical Rehabilitation; Human-Computer Interaction

1. Introduction

The notion of communicating directly with devices or brains via the human central nervous system has long been the domain of science fiction stories. However, with the continued advancement of BCI technology, this communication is becoming a reality by recognizing signals from the central nervous system and utilizing them to execute commands without invoking participation of the peripheral neuromuscular system [1]. The field has its roots dating back to the 1970s and has seen exponential growth in the

last decade due to advances in neurobiology, sensing, and computational techniques. These three disciplines have converged to rapidly push the field from the prototype systems of the lab to systems with real-world application. The field of research for BCI has investigated many aspects of the technology. Early work focused on basic signal acquisition and classification techniques for BCI, such as implementing Common Spatial Pattern (CSP) and Linear Discriminant Analysis (LDA) in motor imagery protocols. In recent years, deep learning techniques such as Convolutional Neural Networks (CNN) and Long Short-Term Memory (LSTM) networks have been utilized to deal with the high-dimensional and nonlinear nature of Electroencephalography (EEG) signals, which results in a significant improvement in decoding accuracy [2]. From a technical standpoint, two main classes exist for BCI: invasive or implantable BCIs such as ElectroCorticography (ECoG) and Utah arrays and non-invasive BCI mainly using scalp recorded EEG. The invasive methods have higher spatial resolution and much higher signal bandwidth at the cost of potential mortality and long term compatibility risks from surgical implantation. Non-invasive methods, safer and easier to deploy, suffer from contaminating signals, low spatial resolution, and sensitivity to environmental artifacts and limited signal bandwidth [3]. Despite the aforementioned progress, numerous challenges remain persistent and pervasive in the current field of research. The success of real-time interaction is hampered by limited accuracy and stability of signals recorded in complex and dynamic real-world conditions. A variety of factors, such as motion of the subject, and electromagnetic interference in the environment, introduce substantial amounts of noise into the recorded EEG signals. There is also considerable variability in EEG signals between and within individuals, which hinders the development of universal applicable calibration methods and leads to often lengthy and subject-specific training procedures. Furthermore, an international consensus has yet to be reached on the ethical, policy, and governance issues introduced by these technologies, such as privacy concerns regarding neural data, potential for mind control by malicious parties, device safety in life-and-death applications, and the legal and moral responsibility for the actions of a BCI user [4]. Without clear international regulations, the development and deployment of these systems faces additional challenges.

Armed with these motivations, the current work aims to provide a comprehensive assessment of the current state of the art in BCI, to demarcate the relative advantages and limitations of the predominant technical routes, and to highlight key challenges and promising fronts for cross-subject implementation. The analytical scheme unfolds along the following lines: first, an overview of the basic concepts and methodologies underlying BCI, second, a critique of representative healthcare and consumer applications through case studies, and third, a suggestion of feasible approaches to meet current technical and ethical challenges of BCI, which may serve as a comprehensive resource guide for practitioners and researchers working in this dynamically evolving domain.

2. Fundamental Components and Core Algorithms

Essentially, a BCI system can be viewed as a closed loop involving five sequential and interacting stages: signal acquisition, preprocessing, feature extraction, pattern classification/decoding, and feedback execution. The primary methodological focus is on applying machine learning techniques to extract meaningful neural intent from background brain signals, which necessitates sophisticated computational algorithms to accommodate the unique nature and non-stationarity of neural data.

Decoding models are the "software" of the BCI which output the practical utility of the BCI by giving classes of intended user commands or state classes their extracted features. There are two main types of models, which have different advantages and use cases.

Traditional Machine Learning Models may be sufficient and computationally efficient for use cases with lower-dimensional, manually engineered feature sets. One of the first algorithms to achieve a motor imagery BCI landmark is the Common Spatial Pattern method (CSP). CSP works by learning spatial filters which maximize the variance of signals from one class while minimizing variance from the other [1]. The resulting variances of the spatially filtered signals are highly discriminative features for the next classification step.

$$\max_{w} \frac{w^T \Sigma_1 w}{w^T \Sigma_2 w} \tag{1}$$

The resulting variances of the spatially filtered signals serve as highly discriminative features for subsequent classification [1]. Another popular model is the Linear Discriminant Analysis (LDA) classifier, which is computationally efficient and finds an optimal projection direction by maximizing the ratio of between-class variance to within-class variance. The decision function for a novel feature vector x is given by:

$$f(x) = w^T x + b \tag{2}$$

where w is the weight vector and b is the bias term. Support Vector Machines (SVMs) are also commonly used due to their ability to generalize well in high-dimensional

ISSN 2959-6157

spaces. Deep Learning Models have recently received considerable attention due to their ability to lift the bottleneck of manually engineering useful hierarchical features from raw or mildly pre-processed EEG signals end-to-end, thus avoiding the pitfalls of manually engineered features and the potential loss of information associated with the feature extraction step. Convolutional Neural Networks (CNN) are able to directly process multi-channel EEG data, typically represented as two-dimensional images (time × channel) or three-dimensional tensors (time × channel × frequency). CNN convolutional layers have been autonomously extracted salient spatiotemporal-spectral features. One lightweight architecture is EEGNet, which has been shown to achieve high performance with drastically fewer trainable parameters while simultaneously requiring minimal computational resources, making it ideal for BCIs with computational constraints or limited training data [2]. When the task requires modeling long-range context and temporal dynamics, such as continuous movement trajectories and fluctuating cognitive load, Long Short-Term Memory (LSTM) networks and Gated Recurrent Units (GRUs) are especially effective at modeling long-term dynamics in sequential data, such as EEG signals. Most recently, self-attention based Transformer architectures have begun to be applied to the EEG decoding task with success.

Most effectiveness and applied usefulness of these models are evaluated by some metrics. Classification Accuracy is a simple metric but Information Transfer Rate (ITR in units of bits/minute, which considers both classification accuracy and the speed of command selection), is usually the standard to evaluate the applied effectiveness of a BCI system [1]. Kappa Coefficient is used to consider chance agreement in classification. Typical applications for algorithm development, benchmarking and validation include internationally public available common datasets (e.g., BCI Competition series, PhysioNet) and data collected by research institutions using commercial high-fidelity EEG apparatus (e.g., NeuroScan, BrainProducts) or even advanced implantable systems (e.g., Neuropixels, which provide an order-of-magnitude improvement in resolution over currently available invasive technology).

3. Application Analysis I: Medical Rehabilitation

Medical RehabilitationRehabilitation is the most obvious and valuable application area of BCI technology. It can provide new treatment options for patients with severe neurological damage. It has a significant impact on communication for stroke and LIS patients or advanced ALS patients after motor function recovery. The core idea is to establish a closed-loop neural feedback training system, allowing patients to drive external devices (such as robotic exoskeletons, FES (functional electrical stimulators, virtual reality avatars), etc.) through volitional imagination activities, thereby promoting the use-dependent plasticity and remodeling of their damaged neural pathways (through the closed-loop feedback training mechanism, stimulating the reorganization and remodeling of the brain) [3]. Its basic principle is that the brain has strong plasticity and can undergo corresponding changes after specific stimulation and practice.

One of its representative applications is the BCI rehabilitation system based on motor imagery in chronic stroke patients [5-6]. The experimental process is shown in Figure 1. The basic process is that patients imagine their limb movements, the BCI system decodes their intentions, and then controls the robotic actuator or FES (functional electrical stimulators) to actually perform or assist in performing the movement, and provides congruent sensory feedback.



Fig. 1 Schematic of the motor imagery-based BCI rehabilitation workflow and a comparison of clinical outcomes between patient groups.

Its core contribution lies in that in a clinical trial of a group of chronic stroke patients using a randomized controlled design, the CSP method was used to extract features and the LDA method was used to achieve classification, and then the subjects' intentions for hand movements were decoded from EEG signals. After the subjects completed 12 weeks of BCI-robot rehabilitation training, the functional recovery of the experimental group patients was significantly better than that of the control group, which received only traditional rehabilitation training, with an average increase in Fugl-Meyer assessment scores of more than 30%. Further, through neuroimaging technology, correlated reorganization of sensorimotor cortex activation patterns was also observed in some subjects, providing a physiological basis for their functional recovery. The main results are shown in Table 1.

Table 1. Comparative analysis of Fugl-Meyer assessment scores pre- and post-rehabilitation

Intervention

Group	Number of patients	Pre-training Fugl-Meyer-Scor (Mean +—SD)	Post-training fugl Meyer Score (Mean+ -SD)	Improvement rate
fuglBCI-Experimental Group	15	28.5+—5.2	39.8+-6.1	39.6%
Conventional Rehabilitation Control Group	15	27.8+—4.9	33.2+-5.5	19.4%

This case has proven that BCI systems based on traditional machine learning models, although the model itself is simple, can still bring about large and meaningful benefits, as long as the BCI can reliably decode meaningful neural features. The key to success does not lie so much in the decoding algorithm itself, but in the BCI's tight coupling with task-oriented and motivating rehabilitation equipment (such as robots, FES, interactive virtual scenes, etc.), which can provide intensive, positive, and repetitive feedback, and thus effectively stimulate use-dependent functional reorganization of the brain's cortical networks. Beyond motor recovery, BCI-based communication systems, usually based on P300 or SSVEP paradigms, can restore the most basic ability of a completely paralyzed person to interact with the environment, allowing the person to spell out words or control the environment through his/

ISSN 2959-6157

her own will, which can dramatically improve the quality of life and self-care of the paralyzed patient.

4. Application Analysis II: Intelligent Interaction and Consumer Electronics

Beyond the medical application focused on the above, the non-invasive BCI is gradually extending to the consumer market, aiming to achieve new types of passively used and highly immersive human-computer interaction methods. It is gradually being applied in fields such as gaming and entertainment (controlling various game content through the player's state), neurofeedback for attention training and mental health, monitoring the state of people in companies (such as whether the driver is sleepy), control of smart homes (controlling the environment through the cognitive state of the user) and other applications. Companies like BrainUp Technology are developing portable and aesthetically designed EEG headbands, representing the trend of consumer form factors of products in this emerging market [7].

Consumer-grade BCI products usually use streamlined machine learning models or simple and efficient deep learning structure in order to achieve real-time computation capability on mobile phones or embedded consumer electronics with limited computing power and battery. The application range usually recognizes the overall state of the user (such as concentration, relaxation state, depth of meditation, specific intentional blink state, etc.), rather than the discrete and precise command control required by medical assistive technology. The value proposition of the product is either to provide users with information about their own cognitive state or to achieve hand-free interaction in certain scenarios.

However, consumer-grade BCI faces a number of different, often much more challenging issues that are much less pronounced in medical or research settings under controlled conditions. Signal quality is often much less than what can be obtained in a clinical environment with research grade equipment and experienced operator. And particularly the challenges due to inter-individual variability are much more pronounced in a mass market application: a model that works well for some individuals may work well for these individuals, but may not work at all for individuals for whom it was not designed, for whom the electrode-skin contact is poor, for whom conductive gel is missing, or for whom ambient electromagnetic noise is unpredictable may cause a catastrophic drop in signal quality with highly variable performance and unreliable model predictions.

In addition, the problem of inter-subject variability is particularly pronounced in a mass-market application. A model that works well for some individuals may work well for these individuals, but may work poorly for individuals for whom it was not designed: for whom the electrode-skin contact is poor, for whom conductive gel is missing, or for whom ambient electromagnetic noise is unpredictable. This may cause a catastrophic drop in signal quality with highly variable performance and unreliable model predictions. To improve robustness and user experience, high-end consumer-grade BCI systems are increasingly employing machine learning strategies such as incremental learning, online adaptive algorithms, or user-initiated calibration routines. These technologies enable continuous refinement of model parameters on the fly using incoming data from the user, thereby adapting to the brain signal characteristics of the user in use. This ability to adapt to and calibrate the individual user represents a key enabling technology that must be overcome for successful real-world deployment outside of the lab [8].

The need to operate outside the home sphere also drives innovation in dry electrode technology and discreet form factors to address issues of user comfort, social acceptability, and long-term wearability.

5. Limitations and Future Outlook

5.1 Limitations

The present study, and the BCI field broadly, continues to grapple with several formidable challenges that currently constrain its widespread adoption and reliability:

1. Persistent Technical Bottlenecks: The intrinsic physical and physiological constraints of non-invasive BCIs concerning poor signal-to-noise ratio, limited spatial resolution, and vulnerability to artifacts resist fundamental resolution. Signal quality remains the primary bottleneck for robust non-invasive systems. Conversely, while invasive BCIs offer superior signal quality, they face persistent and significant issues regarding long-term biocompatibility, structural stability of the neural tissue-electrode interface, and signal consistency over months or years. For instance, the foreign body response often leads to glial scar formation around implanted microelectrodes, which typically results in progressive signal attenuation and eventual loss of viable recording sites over time [3]. The development of chronically stable, high-bandwidth neural interfaces remains a major hurdle.

2. Algorithmic Generalizability and Calibration Burden: Contemporary decoding models, particularly those achieving high accuracy, often exhibit a heavy reliance on extensive user-specific calibration data collected in controlled sessions. Their capacity to maintain performance

across different recording sessions for the same user (inter-session stability) and, more critically, across diverse users (inter-subject generalizability) remains generally unsatisfactory. This "calibration bottleneck" is a significant barrier to plug-and-play BCI systems. The development of robust, zero-shot or few-shot cross-subject adaptive algorithms requiring minimal or no calibration stands as one of the most pressing and actively pursued objectives in contemporary BCI research [8].

3. Ethical, Security, and Societal Risks: Neural data, encompassing an individual's intentions, emotional states, and potentially private thoughts, arguably constitutes the most intimate and sensitive form of personal privacy. Globally, comprehensive and enforceable regulatory frameworks governing its collection, secure encrypted storage, permissible usage, and clear ownership rights are still underdeveloped. The potential for malicious hacking, unauthorized surveillance, or manipulation of neural signals presents unprecedented security threats and profound ethical quandaries [4]. Furthermore, ensuring device safety and reliability (e.g., preventing unintended false triggers in critical applications) is paramount, particularly for life-affecting applications such as wheelchair control or motor neuroprosthetics. Broader societal questions concerning cognitive enhancement, identity, and equitable access to these technologies also demand urgent and inclusive public discourse.

5.2 Future Outlook

The continued evolution and integration of BCI technology into society are anticipated to concentrate on several interconnected key fronts, driven by interdisciplinary innovation:

1. Technological Integration and Material Innovation: Future progress will likely hinge on synergistic advancements. This encompasses the development of next-generation flexible, highly biocompatible, and minimally inflammatory implantable electrodes using novel materials like graphene or polymer-based probes to enhance long-term stability and signal yield. For non-invasive systems, the exploration of hybrid Brain-Computer Interface (hBCI) systems, merging complementary modalities such as EEG with functional near-infrared spectroscopy (fNIRS)- which provides hemodynamic information-or with eye-tracking, can compensate for their respective weaknesses and provide a more robust multi-modal assessment of user state [2, 8]. Simultaneously, the application of cutting-edge AI paradigms such as transfer learning, meta-learning, and few-shot learning is poised to make significant inroads into addressing the pervasive model calibration and generalization hurdles, potentially enabling systems that can rapidly adapt to new users with minimal data.

2. Deepening and Expanding Application Scenarios: Transcending the current primary focus on medical rehabilitation and niche consumer applications, BCI harbors significant potential for integration into a wider array of sectors. In aerospace and transportation, BCIs could be deployed for monitoring pilot/driver cognitive states, vigilance, and fatigue in real-time to enhance safety. In education, they could facilitate real-time attention assessment and enable personalized learning pathways adapted to the student's cognitive engagement level [9]. The field of neuromarketing might employ BCIs for more direct assessment of consumer engagement and emotional responses. A long-term aspiration for consumer BCI development involves achieving seamless, intuitive, and nearly imperceptible integration into daily interactions, perhaps through advanced hearable or wearable technologies.

3. Standardization, Ethical Governance, and Public Engagement: As BCI technologies mature, an urgent imperative exists to advance the establishment of globally harmonized technical standards and ethical guidelines for neural data security, privacy protection, and device safety. The formulation of multidisciplinary ethical review frameworks and oversight committees, involving ethicists, neuroscientists, engineers, and legal experts, is essential to steer technology development along responsible and socially beneficial trajectories. Moreover, enhancing public scientific communication and fostering inclusive engagement on the societal implications of BCI are critical for building trust and fostering a well-informed societal consensus regarding the acceptable development, deployment, and use of this potent and transformative technology [4]. Proactive policy development is needed to keep pace with technological change.

6. Conclusion

This review has provided a systematic analysis of the present developmental status and application horizons of brain-computer interface technology. The inquiry confirms that BCI has evolved along distinct technological pathways, primarily differentiated by the degree of invasiveness, with its core intelligence embedded in the sophisticated interpretation of neural signals using a spectrum of models spanning traditional machine learning to contemporary deep learning architectures. Through the implementation of closed-loop neural feedback systems, BCI has substantiated its remarkable effectiveness in medical rehabilitation, actively promoting functional recovery and restoring communication capabilities, thereby offering new hope for patients with severe neurological conditions. Within the consumer sphere, it seeks to pioneer innovative

ISSN 2959-6157

forms of human-computer interaction, albeit its advancement is presently tempered by significant obstacles related to signal quality, hardware usability, and individual variability.

Although confronted by multifaceted challenges spanning technical limitations, algorithmic generalizability, and profound ethical safety concerns, the trajectory of BCI is one of rapid innovation. Continued synergistic progress across materials science, algorithmic innovation, neuroscience, and ethical governance is poised to progressively mature brain-computer interface technology, gradually overcoming current barriers. This confluence of advancements ultimately carries the potential to position BCI as a transformative instrument not only for restoring lost function but also for augmenting human capacities, deepening our understanding of the brain, and elevating the overall quality of life in ways previously confined to the realm of imagination. The journey from laboratory curiosity to impactful real-world technology is well underway, demanding a concerted and responsible effort from the global research community and society at large.

References

[1] Wolpaw J R, Birbaumer N, McFarland D J, Pfurtscheller G, Vaughan T M. Brain–computer interfaces for communication and control. Clinical Neurophysiology, 2002, 113(6): 767–791.

[2] Lawhern V J, Solon A J, Waytowich N R, Gordon S M, Hung C P, Lance B J. EEGNet: A compact convolutional neural network for EEG-based brain–computer interfaces. Journal of Neural Engineering, 2018, 15(5): 056013.

[3] Lebedev M A, Nicolelis M A. Brain–machine interfaces: From basic science to neuroprostheses and neurorehabilitation. Physiological Reviews, 2017, 97(2): 767–837.

[4] Ienca M, Haselager P. Hacking the brain: Brain–computer interfacing technology and the ethics of neurosecurity. Ethics and Information Technology, 2016, 18(2): 117–129.

[5] Urigüen J A, Garcia-Zapirain B. EEG artifact removal—state of the art and guidelines. Journal of Neural Engineering, 2015, 12(3): 031001.

[6] Ang K K, Guan C, Phua K S, Wang C, Zhou L, Tang K Y, Chua K S. Brain–computer interface-based robotic end-effector system for wrist and hand rehabilitation: Results of a three-armed randomized controlled trial for chronic stroke. Frontiers in Neuroengineering, 2014, 7: 30.

[7] BrainUp. BrainUp Smart EEG Sleep Device white paper. 2022.

[8] Jayaram V, Alamgir M, Altun Y, Schölkopf B, Grosse-Wentrup M. Transfer learning in brain–computer interfaces. IEEE Computational Intelligence Magazine, 2016, 11(1): 20–31.

[9] Gao Yuan, Li Xiaoyu, Ming Dong. Advances in deep learning-based EEG decoding methods. Chinese Journal of Biomedical Engineering, 2021, 40(3): 357–365.